



# Clingtex<sup>®</sup>

## Chain lubricant

### Product description

Clingtex is a power saw cutting chain lubricant, specially formulated with quality solvent refined oils and additives designed to optimise adhesion, helping prevent wear, corrosion, rust and lubricant foaming and fling-off during tree felling operations.

Clingtex can also be used as a long-term lubricating oil and offers durable cutting chain protection.

### Customer benefits

- Designed for good anti-wear performance for reliable and extended chain service life
- Offers oxidation resistance to help prevent varnish and deposits forming in chain links
- Provides rust and corrosion protection for chain links, guides and saw teeth
- Tackiness feature helps give good adhesion to the chain in operation
- Formulated to offer ease of use in service

### Product highlights

- **Designed for good anti-wear performance**
- **Formulated for oxidation resistance**
- **Provides rust and corrosion protection**
- **Tackiness feature helps adhesion**
- **Offers ease of use in service**

## Applications

- Clingtex is widely used throughout the lumber, tree-felling and tree-surgery industries and carries the recommendation of many manufacturers of power saws.
- Clingtex is recommended for the lubrication of cutting chains on power saws. It may be applied directly to the chain using an oil-can or filled into the reservoir which automatically lubricates the chain. This product is suitable for the chain lubrication of many types and sizes of power chain saw, whether engine or electrically driven.
- Clingtex can also be used for many drive, control and transport chains, where an oil is needed with good adherence to metal.
- It is important to remember that Clingtex is not suitable for engine lubrication, therefore it should never be used to fill or to top-up the engine crankcase.

Typical test data				
Test	Test Methods	Results		
Viscosity Grade		55	125	180
<b>Shelf Life: 60 months from date of filling indicated on the product label.</b>				
Oil Type		Mineral	Mineral	Mineral
Kin. Viscosity at 40°C, mm <sup>2</sup> /s	ISO 3104	55	125	180
Kin. Viscosity at 100°C, mm <sup>2</sup> /s	ISO 3104	7.3	12.6	16
Viscosity Index	ISO 2909	>90	>90	>90
Density at 15°C, kg/l	ASTM D 1298	0.878	0.888	0.890
Flash point, COC, °C	ISO 2592	182	182	182
Pour Point, °C	ISO 3015	-30	-27	-18

In some cases, Way Lubricant X range can be used as mineral chain saw oils. They have different concentrations of tackifier.

The information given in the typical data does not constitute a specification but is an indication based on current production and can be affected by allowable production tolerances. The right to make modifications is reserved. This supersedes all previous editions and information contained in them.

**Disclaimer** Chevron accepts no liability for any loss or damage suffered as a result of using this product for any application other than applications specifically stated in any Product Data Sheet's.

**Health, safety, storage and environmental** Based on current available information, this product is not expected to produce adverse effects on health when used for the intended application and in accordance with the recommendations provided in the Material Safety Data Sheet (MSDS). MSDS's are available upon request through your local sales office, or via the Internet. This product should not be used for purposes other than its intended use. When disposing of used product, take care to protect the environment and follow local legislation.

**A Chevron company product**