

# Safety Data Sheet

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

#### Techron D Concentrate

Product Number(s): 804525

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: Diesel fuel additive

### 1.3 Details of the supplier of the safety data sheet

Uno-X Smørelie A/S

Buddingevej 195

DK-2860 Søborg

Kundecenter: +45 70 11 56 78

Denmark

Web: lube.unox.dk

email : sales@unox.dk

### 1.4 Emergency telephone number

#### Transportation Emergency Response

CHEMTREC: +1 703 527 3887

#### Health Emergency

Danish Environmental Protection Agency: +45 72 54 40 00Chevron Emergency Information Center:

International calls accepted 24 hours: +1 510 231 0623

Poison Control Centre Denmark: 0045/ 82 12 12 12

#### Product Information

Technical Information: 0045/70 11 56 78

## SECTION 2 HAZARDS IDENTIFICATION

### 2.1 Classification of the substance or mixture

#### CLP CLASSIFICATION:

- Aspiration toxicant: Category 1, H304; May be fatal if swallowed and enters airways.
- Target organ toxicant (central nervous system): Category 3, H336; May cause drowsiness or dizziness.
- Chronic aquatic toxicant: Category 2, H411; Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

Under the criteria of Regulation (EC) No 1272/2008 (CLP):



Signal Word: Danger

## HAZARD STATEMENTS:

### Health Hazards:

- May be fatal if swallowed and enters airways (H304).
- May cause drowsiness or dizziness (H336).
- Repeated exposure may cause skin dryness or cracking (EUH066).

### Environmental Hazards:

- Toxic to aquatic life with long lasting effects (H411).

- contains: Distillates (petroleum), hydrotreated light

## PRECAUTIONARY STATEMENTS:

### General:

- Keep out of reach of children (P102).

### Prevention:

- Avoid breathing dust/fume/gas/mist/vapours/spray (P261).

### Response:

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician (P301+P310).
- Do NOT induce vomiting (P331).

### Storage:

- Store locked up (P405).

### Disposal:

- Dispose of contents/container in accordance with applicable local/regional/national/international regulations (P501).

## 2.3 Other hazards

This product is not, or does not contain, a substance that is a potential PBT or a vPvB. This product is not, or does not contain, a substance that potentially has endocrine disrupting properties.

## SECTION 3 COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.2 Mixtures

This material is a mixture.

COMPONENTS	CAS NUMBER	EC NUMBER	REGISTRATION NUMBER	CLP CLASSIFICATION	AMOUNT
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	01-2119484819-18	Asp. Tox. 1/H304; STOT SE 3/H336	50 - 60 %weight
2-ethylhexyl nitrate	Trade secret	248-363-6	01-2119539586-27	Acute Tox. 4/H312; Aquatic Chronic 2/H411	20 - 30 %weight
2-Ethylhexan-1-ol	104-76-7	203-234-3	01-2119487289-20	Eye Irrit. 2/H319; Acute Tox. 4/H302; Skin Irrit. 2/H315; STOT SE 3/H335; Acute Tox. 4/H332	1 - 5 %weight

The full text of all CLP H-statements is shown in Section 16.

## SECTION 4 FIRST AID MEASURES

### 4.1 Description of first aid measures

**Eye:** No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

**Skin:** Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, use soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

**Ingestion:** If swallowed, get immediate medical attention. Do not induce vomiting. Never give anything by mouth to an unconscious person.

**Inhalation:** Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue.

#### **4.2 Most important symptoms and effects, both acute and delayed**

##### **IMMEDIATE SYMPTOMS AND HEALTH EFFECTS**

**Eye:** Not expected to cause prolonged or significant eye irritation.

**Skin:** Skin contact may cause drying or defatting of the skin. Symptoms may include pain, itching, discoloration, swelling, and blistering.

**Ingestion:** Because of its low viscosity, this material can directly enter the lungs, if swallowed, or if subsequently vomited. Once in the lungs it is very difficult to remove and can cause severe injury or death.

**Inhalation:** Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

**DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS:** Not classified.

#### **4.3 Indication of any immediate medical attention and special treatment needed**

**Note to Physicians:** Ingestion of this product or subsequent vomiting may result in aspiration of light hydrocarbon liquid, which may cause pneumonitis.

### **SECTION 5 FIRE FIGHTING MEASURES**

#### **5.1 Extinguishing media**

Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

#### **5.2 Special hazards arising from the substance or mixture**

**Combustion Products:** Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion. Combustion may form oxides of Nitrogen .

#### **5.3 Advice for firefighters**

This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### **6.1 Personal precautions, protective equipment and emergency procedures**

Eliminate all sources of ignition in vicinity of spilled material. Refer to Sections 5 and 8 for more information.

#### **6.2 Environmental precautions**

Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater.

#### **6.3 Methods and material for containment and cleaning up**

Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use

appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil and dispose of in a manner consistent with applicable requirements. Place other contaminated materials in disposable containers and dispose of in a manner consistent with applicable requirements. Report spills to local authorities as appropriate or required.

#### 6.4 Reference to other sections

See sections 8 and 13.

### SECTION 7 HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

**General Handling Information:** The maximum handling temperature is 50°C. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

**Precautionary Measures:** Storage, processing, handling, and use at temperatures above the flash point can produce ignitable vapors if the liquid is released or vessels are vented. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not breathe vapor or fumes. Wash thoroughly after handling.

**Static Hazard:** Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

**Container Warnings:** Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

#### 7.2 Conditions for safe storage, including any incompatibilities

**General Storage Information:** The maximum storage temperature is 45°C.

#### 7.3 Specific end use(s): Diesel fuel additive

### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the workplace when designing engineering controls and selecting personal protective equipment (PPE). If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, refer to PPE information below.

Factors that affect PPE include, but are not limited to: properties of the chemical, other chemicals which may contact the same PPE, physical requirements (fit & sizing, cut/puncture protection, dexterity, thermal protection, etc.), and potential allergic reactions to the PPE material. It is the responsibility of the user to read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

#### 8.1 Control parameters

##### Occupational Exposure Limits:

Component	Country/ Agency	Form	TWA	STEL	Ceiling	Notation
2-Ethylhexan-1-ol	Denmark	--	5.4 mg/m <sup>3</sup>	--	--	--
2-Ethylhexan-1-ol	EU-Indicative	--	5.4 mg/m <sup>3</sup>	--	--	--

Consult local authorities for appropriate values.

## 8.2 Exposure controls

### ENGINEERING CONTROLS:

Use general ventilation, local exhaust ventilation, or a combination of both.

### PERSONAL PROTECTIVE EQUIPMENT

**Eye/Face Protection:** Wear protective equipment to prevent eye contact. Selection of protective equipment may include safety glasses, chemical goggles, face shields, or a combination depending on the work operations conducted.

**Skin Protection:** Wear chemical personal protective equipment (PPE) to prevent skin contact. Selection of chemical protective clothing should be performed by an Occupational Hygienist or Safety Professional and be based upon applicable standards (ASTM F739 or EN 374). Using chemical PPE depends upon operations conducted and may include chemical gloves, boots, chemical apron, chemical suit, and complete facial protection. Refer to PPE manufacturers to obtain breakthrough time information to determine how long PPE can be used before it needs to be replaced. Unless specific glove manufacturer data indicates otherwise, the below table is based upon available industry data to assist in the glove selection process and is intended to be used as reference only.

Chemical Glove Material	Thickness (mm)	Typical Breakthrough Time (minutes)
Butyl	0.7	5
Neoprene	0.61	15
Nitrile	0.5	120
Nitrile	0.11	5
Polyvinyl Chloride (PVC)	0.7	5
Viton Butyl	0.3	240

**Respiratory Protection:** Determine if airborne concentrations are below the recommended occupational exposure limits for jurisdiction of use. If airborne concentrations are above the acceptable limits, wear an approved respirator that provides adequate protection from this material, such as: Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

### ENVIRONMENTAL EXPOSURE CONTROLS:

See relevant Community environmental protection legislation or the Annex, as applicable.

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

**Attention: the data below are typical values and do not constitute a specification.**

### 9.1 Information on basic physical and chemical properties

#### Appearance

**Color:** Amber

**Physical State:** Liquid

**Odor:** Characteristic

**Odor Threshold:** No data available

**pH:** Not Applicable

**Melting Point:** No data available

**Freezing Point:** No data available

**Initial Boiling Point:** No data available

**Flashpoint:** (Pensky-Martens Closed Cup) 66 °C (151 °F) (Typical)

**Evaporation Rate:** No data available

**Flammability (solid, gas):** Not Applicable

**Flammability (Explosive) Limits (% by volume in air):**

Lower: Not Applicable Upper: Not Applicable

**Vapor Pressure:** No data available

**Relative Vapor Density:** No data available  
**Relative Density:** 0.867 (Typical) @ 15.6°C (60°F)  
**Density:** No data available  
**Solubility:** Soluble in hydrocarbons; insoluble in water  
**Partition coefficient n-octanol/water (logarithmic value):** No data available  
**Auto-ignition temperature:** No data available  
**Decomposition temperature:** No data available  
**Kinematic Viscosity:** 2.8 mm<sup>2</sup>/s @ 40°C (104°F) (Typical)  
**Explosive Properties:** No Data Available  
**Oxidising properties:** No Data Available

**9.2 Other Information:** No Data Available

## SECTION 10 STABILITY AND REACTIVITY

**10.1 Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

**10.2 Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

**10.3 Possibility of hazardous reactions:** Hazardous polymerization will not occur.

**10.4 Conditions to Avoid:** Not applicable

**10.5 Incompatible materials to avoid:** Not applicable

**10.6 Hazardous decomposition products:** None known (None expected)

## SECTION 11 TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information:

**Serious Eye Damage/Irritation:** The material is not considered an eye irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Skin Corrosion/Irritation:** The material is not considered a skin irritant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Skin Sensitization:** The material is not considered a skin sensitizer. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Dermal Toxicity:** The material is not considered a dermal toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Toxicity Estimate (dermal):** Not Applicable

**Acute Oral Toxicity:** The material is not considered an oral toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Toxicity Estimate (oral):** 10000 mg/kg

**Acute Inhalation Toxicity:** The material is not considered an inhalation toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Acute Toxicity Estimate (inhalation):** Not Applicable

**Germ Cell Mutagenicity:** The material is not considered a mutagen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Carcinogenicity:** The material is not considered a carcinogen. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Reproductive Toxicity:** The material is not considered a reproductive toxicant. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Single Exposure:** This material may cause drowsiness or dizziness. The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Specific Target Organ Toxicity - Repeated Exposure:** The material is not considered a target organ toxicant (repeated exposure). The product has not been tested. The statement is based on evaluation of data for similar materials or product components.

**Aspiration Hazard:** This material is considered an aspiration hazard based on the kinematic viscosity of the material.

**Component Information:**

<b>Serious Eye Damage/Irritation:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Test Result: Causes eye irritation

<b>Skin Corrosion/Irritation:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Test Result: Causes skin irritation

<b>Skin Sensitization:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Acute Dermal Toxicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Test Qualifier: LD50 Test Result: 1000-2000 mg/kg Species: rabbit
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Acute Oral Toxicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Test Qualifier: LD50 Test Result: 300-2000 mg/kg Species: rat

<b>Acute Inhalation Toxicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Test Qualifier: LC50 Test Result: 10-20 mg/l Species: rat Duration:--

<b>Germ Cell Mutagenicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met

2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Carcinogenicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Reproductive Toxicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Specific Target Organ Toxicity - Single Exposure:</b>	
Distillates (petroleum), hydrotreated light	Test Result: May cause drowsiness or dizziness
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Test Result: May cause respiratory irritation

<b>Specific Target Organ Toxicity - Repeated Exposure:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Based on available data, the classification criteria are not met
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

## 11.2 Information on other hazards

No other hazards identified.

## SECTION 12 ECOLOGICAL INFORMATION

### Product Information:

#### 12.1 Toxicity

This material is expected to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment. The product has not been tested. The statement has been derived from the properties of the individual components.

#### 12.2 Persistence and degradability

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

#### 12.3 Bioaccumulative potential

Bioconcentration Factor: No Data Available

Partition coefficient n-octanol/water (logarithmic value): No data available

#### 12.4 Mobility in soil

No data available.

#### 12.5 Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a potential PBT or a vPvB.

#### 12.6 Endocrine Disrupting Properties

This mixture does not contain any substances that are assessed as having endocrine disrupting properties.

#### 12.7 Other adverse effects

No other adverse effects identified.



**Component Information:**

<b>Acute Toxicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Protocol: OECD 201-Alga Growth Inhib Test Qualifier: EC50 (growth rate) Test Result: 3.22 mg/l Species: Algae Duration:72 hour(s)
2-ethylhexyl nitrate	Protocol: OECD 202-Daphnia Immob/Repro Test Qualifier: LC50 Test Result: >12.6 mg/l Species: Invertebrate Duration:48 hour(s)
2-ethylhexyl nitrate	Protocol: OECD 203-Fish Acute Tox Test Qualifier: LC50 Test Result: 2 mg/l Species: Fish Duration:96 hour(s)
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Long-term Toxicity:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	No test data available
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Biodegradation:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	Test Result: Not readily biodegradable Biodegradation: 0%
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

<b>Bioaccumulative Potential:</b>	
Distillates (petroleum), hydrotreated light	Based on available data, the classification criteria are not met
2-ethylhexyl nitrate	No test data available
2-Ethylhexan-1-ol	Based on available data, the classification criteria are not met

**SECTION 13 DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by international, country, or local laws and regulations. In accordance with European Waste Catalogue (E.W.C.) the codification is the following:07 07 99

**SECTION 14 TRANSPORT INFORMATION**

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

**ADR/RID**

**14.1 UN Number or ID Number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate)

**14.3 Transport hazard class(es):** 9

**14.4 Packing group:** III

**14.5 Environmental hazards:** Yes (2-Ethylhexyl nitrate)

**14.6 Special precautions for user:** Road Tunnel Restriction Code: (-); Hazard ID No: 90  
ADR CODE M6; PACKAGES CONTAINING LESS THAN 5 LITERS IN ONE PACKAGING MAY BE EXEMPT FROM REGULATION

## ICAO / IATA

**14.1 UN Number or ID Number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate)

**14.3 Transport hazard class(es):** 9

**14.4 Packing group:** III

**14.5 Environmental hazards:** Yes (2-Ethylhexyl nitrate)

**14.6 Special precautions for user:**

PACKAGES CONTAINING LESS THAN 5 LITERS IN ONE PACKAGING MAY BE EXEMPT FROM REGULATION

## IMO / IMDG

**14.1 UN Number or ID Number:** UN3082

**14.2 UN proper shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-Ethylhexyl nitrate)

**14.3 Transport hazard class(es):** 9

**14.4 Packing group:** III

**14.5 Environmental hazards:** MARINE POLLUTANT(2-Ethylhexyl nitrate)

**14.6 Special precautions for user:**

PACKAGES CONTAINING LESS THAN 5 LITERS IN ONE PACKAGING MAY BE EXEMPT FROM REGULATION

**14.7 Maritime Transport in Bulk according to IMO Instruments:** Not applicable

## SECTION 15 REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture REGULATORY LISTS SEARCHED:

01=EU Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances.

02=EU Directive 90/394/EEC: Carcinogens at work.

03=EU Directive 92/85/EEC: Pregnant or breastfeeding workers.

04=EU Directive 2012/18/EU: Seveso III.

05=EU Directive 98/24/EC: Chemical agents at work.

06=EU Directive 2004/37/EC: On the protection of workers.

07=EU Regulation EC No. 689/2008: Annex 1, Part 1.

08=EU Regulation EC No. 689/2008: Annex 1, Part 2.

09=EU Regulation EC No. 689/2008: Annex 1, Part 3.

10=EU Regulation EC No. 850/2004: Prohibiting and restricting persistent organic pollutants (POPs).

11=EU REACH, Annex XVII: Restrictions on manufacture, placing on the market and use of certain dangerous substances, mixture & article.

12=EU REACH, Annex XIV: Authorization List or Candidate List of Substances of Very High Concern for Authorization (SVHC).

The following components of this material are found on the regulatory lists indicated.

Distillates (petroleum), hydrotreated light 04, 05

### CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AIIIC (Australia), DSL (Canada), EINECS (European Union), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States).

## 15.2 Chemical safety assessment

No chemical safety assessment.

### SECTION 16 OTHER INFORMATION

**REVISION STATEMENT:** This is a new Safety Data Sheet. No revision information

**Revision Date:** September 06, 2023

#### Full text of CLP H-statements:

Asp. Tox. 1/H304; May be fatal if swallowed and enters airways  
Acute Tox. 4/H312; Harmful in contact with skin  
Aquatic Chronic 2/H411; Toxic to aquatic life with long lasting effects  
Eye Irrit. 2/H319; Causes serious eye irritation  
Acute Tox. 4/H302; Harmful if swallowed  
Skin Irrit. 2/H315; Causes skin irritation  
STOT SE 3/H336; May cause drowsiness or dizziness  
STOT SE 3/H335; May cause respiratory irritation  
Acute Tox. 4/H332; Harmful if inhaled

#### ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
CVX - Chevron	CAS - Chemical Abstract Service Number
NQ - Not Quantifiable	

Prepared according to the EU Regulation 1907/2006 (as amended) by Chevron Technical Center, 6001 Bollinger Canyon Road, San Ramon, CA 94583.

**The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.**

**No Annex**