

Outboard Gear Oil EP 90
2020-08-06
61018

Page:	1/11
Last revised date:	2024-03-25
SDS-ID:	EU-EN/4.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: Supersedes date: Product No.:

Product name: Outboard Gear Oil EP 90

1.2. Relevant identified uses of the substance or mixture and uses advised against

www.olje.unox.no

Gear oil.

Application:

1.3. Details of the supplier of the safety data sheet

<u>Supplier:</u>	Uno-X Smøreolie A/S Buddingevej 195 DK-2860 Søborg Tel: +45 7011 5678 <u>teknik@unox.dk</u> https://lube.unox.dk/
<u>Supplier:</u>	Uno-X Smøreolje AS Gladengveien 2 NO-0661 Oslo Tel: 04210 / +47 95 05 96 18 <u>olje@unox.no</u>

Responsible for safety	
data sheet authoring:	teknik@unox.dk

1.4. Emergency telephone number

Emergency telephone:

Poison Control Centers are available in specific member countries.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture		
<u>CLP:</u>	The product is not classified.	
2.2. Label elements		
	The substance/mixture does not meet the criteria for classification, but the following labelling must be applied:	
	Contains Amines, C12-14-tert-alkyl. May produce an allergic reaction. Safety data sheet available on request.	
2.3. Other hazards		
<u>PBT/vPvB:</u>	No information available.	
Endorine disrupting properties	This product does not contain any substance identified as having endocrine disrupting properties.	
<u>Other:</u>	Degreasing to skin. Prolonged or repeated contact with skin may cause redness, itching, irritation, eczema, skin cracking and oil acne. The harmful effects may increase in used oil. Oil spills are generally hazardous to the environment.	

Product name:	Outboard Gear Oil EP 90	Page:	2/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

The product contains: mineral oil and additives.

CLP:

<u>%:</u>	CAS-No.:	EC No.:	<u>REACH Reg.</u> <u>No:</u>	Chemical name:	Hazard classification/ SCL:	Notes:
70-99	-		-	Highly refined mineral oil (C15 - C50)	-	L
0,1 - < 0,25	68955-53-3	701-175-2	01-2119456798-18	Amines, C12-14-tert-alkyl	Acute Tox. 2;H330 Acute Tox. 3;H311 Acute Tox. 4;H302 Skin Corr. 1;H314 Eye Dam. 1;H318 Skin Sens. 1A;H317/ C≥6.8 STOT SE 3;H336 Aquatic Acute 1;H400/	

References: The full text for all hazard statements is displayed in section 16.

Notes: L: DMSO < 3% (IP 346)

Contains one or more of the following EINECS-numbers: 265-090-8, 265-091-3, 265-096-0, 265-097-6, 265-098-1, 265-101-6, 265-155-0, 265-156-6, 265-157-1, 265-158-7, 265-159-2, 265-160-8, 265-166-0, 265-169-7, 265-176-5, 276-736-3, 276-737-9, 276-738-4, 278-012-2.

M(ac)=1

M(chr)=1

Aquatic Chronic 1:H410/

Contains one or more of the following REACH registration numbers: 01-2119488706-23, 01-2119487067-30, 01-2119487081-40, 01-2119483621-38, 01-2119480374-36, 01-2119488707-21, 01-2119467170-45, 01-2119480375-34, 01-2119484627-25, 01-2119480132-48, 01-2119487077-29, 01-2119489287-22, 01-2119480472-38, 01-2119471299-27, 01-2119485040-48, 01-2119555262-43, 01-2119495601-36, 01-2119474889-13, 01-2119474878-16.

Product name:	Outboard Gear Oil EP 90	Page:	3/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures		
Inhalation:	Move into fresh air and keep at rest. In case of persistent throat irritation or coughing or after inhalation of oil mist: Seek medical attention and bring along these instructions.	
<u>Skin contact:</u>	Remove contaminated clothing immediately and wash skin with soap and water. In case of rashes, wounds or other skin disorders: Seek medical attention and bring along these instructions.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical attention and bring along these instructions.	
Ingestion:	Immediately rinse mouth and drink 1-2 glasses of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Immediate transport to hospital. Bring along these instructions.	
	Risk of chemical pneumonia after aspiration. Be aware that symptoms of chemical pneumonia may occur several hours after exposure.	

4.2. Most important symptoms and effects, both acute and delayed

<u>Symptoms/effects:</u> See section 11 for more detailed information on health effects and symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Treat symptomatically, no specific antidote

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
	Small fires: Extinguish with carbon dioxide or dry powder.
	Larger fires: Extinguish with foam, carbon dioxide or dry powder.

5.2. Spec	ial hazards arising	from the	substance or	mixture

<u>Specific hazards:</u> During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Protective equipment for fire-	Selection of respiratory protection for fire fighting: follow the general fire
fighters:	precautions indicated in the workplace.

Product name:	Outboard Gear Oil EP 90	Page:	4/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions:	Avoid inhalation of oil mist and contact with skin and eyes. Mark the spillage. In case of spills, beware of slippery floors and surfaces. Follow precautions for safe handling described in this safety data sheet.
6.2. Environmental precaution	<u>15</u>
Environmental precautions:	Do not discharge into drains, water courses or onto the ground.
6.3. Methods and material for	containment and cleaning up
Methods for cleaning up:	Absorb spillage with oil-absorbing material. Clean contaminated area with oil- removing material. Inform Authorities if large amounts are involved.
	removing material. Inform Authorities if large amounts are involved.

6.4. Reference to other sections

References:	For personal protection, see section 8.
	For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Safe handling advice:	Avoid prolonged and repeated contact with oil, particularly used oil. Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into pockets. In case of spills, beware of slippery floors and surfaces. Observe good chemical hygiene practices.
Technical measures:	Use work methods which minimise oil mist production.
Technical precautions:	When working with heated oil, mechanical ventilation may be required.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures for safe	No special precautions.
storage:	
Storage conditions:	Store in tightly closed original container.

7.3. Specific end use(s)

<u>Specific use(s):</u> No information available.

Product name:	Outboard Gear Oil EP 90	Page:	5/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

EU: No occupational exposure limit assigned. Please note that there may be national occupational exposure limits.

8.2. Exposure controls

Engineering measures:	Provide adequate ventilation and minimize the risk of inhalation of vapours and oil mist. Provide access to washing facilities incl. soap, skin cleanser and fatty cream.
Personal protection:	Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Respiratory equipment:	In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P3) can be used.
Hand protection:	Risk of splashes: Wear protective gloves. Butyle: Thickness: 0,7 mm. Breakthrough time: ~120 min. Nitrile: Thickness: 0,8 mm. Breakthrough time: ~240 min. Viton Butyle: Thickness: 0,3 mm. Breakthrough time: ~240 min. Other types of gloves can be recommended by the glove supplier. The most suitable glove must be chosen in collaboration with the supplier of gloves, who can inform about the breakthrough time of the glove material.
Eye protection:	Risk of contact: Wear goggles/face shield.
Hygiene measures:	Wash hands after contact. Wash contaminated clothing before reuse.
Environmental Exposure Controls:	Not available.

Product name:	Outboard Gear Oil EP 90	Page:	6/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Brown to yellow liquid.
Oil smell.
No information available.
Initial boiling point: >315 °C
200 - 235 °C (Cleaveland open cup)
No information available.
No data available.
No data available.
0.8765 - 0.8845 kg/l @15°C (typical)
Soluble in: Organic solvents. Not soluble in water.
No data available.
No data available.
No data available.
61.20 mm²/s - 748 mm²/s @40°C
No data available.
No data available.
None known.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity	
Reactivity:	Not reactive.
10.2. Chemical stability	
<u>Stability:</u>	Stable under normal temperature conditions.
10.3. Possibility of hazardous	s reactions
Hazardous Reactions:	None known.
10.4. Conditions to avoid	
Conditions/materials to avoid:	Heat, sparks, flames.
10.5. Incompatible materials	
Incompatible materials:	Strong oxidizing substances. Strong acids.
10.6. Hazardous decompositio	n products
Hazardous decomposition products:	None in particular.

Product name:	Outboard Gear Oil EP 90	Page:	7/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

The harmful effects may increase in used oil.

Acute Toxicity (Oral):	Based on available data, the classification criteria are not met.
Acute Toxicity (Dermal):	Based on available data, the classification criteria are not met.
Acute Toxicity (Inhalation):	Based on available data, the classification criteria are not met.
Skin Corrosion/Irritation:	Based on available data, the classification criteria are not met.
Serious eye damage/irritation:	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation:	Based on available data, the classification criteria are not met.
Germ cell mutagenicity:	Based on available data, the classification criteria are not met.
Carcinogenicity:	Based on available data, the classification criteria are not met.
Reproductive Toxicity:	Based on available data, the classification criteria are not met.
STOT - Single exposure:	Based on available data, the classification criteria are not met.
STOT - Repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Inhalation:	Inhalation of oil mist or vapours formed during heating of the product will irritate the respiratory system and provoke coughing.
Skin contact:	Degreasing. Prolonged or frequent contact may cause redness, itching, irritation, eczema, skin cracking and oil acne.
	The product contains a small amount of sensitising substance which may provoke an allergic reaction among sensitive individuals.
Eye contact:	Splashes may irritate.
Ingestion:	May irritate and cause malaise.
Specific effects:	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis and skin cancer.

11.2. Information on other hazards

Endocrine disrupting	The product does not contain any substance identified as having endocrine
properties:	disrupting properties.

Product name:	Outboard Gear Oil EP 90	Page:	8/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicit

<u>12.1. Toxicity</u>	
Ecotoxicity:	There are no data on the ecotoxicity of this product. Oil spills are generally hazardous to the environment. The product is not miscible with water and will spread on the water surface.
12.2. Persistence and degrad	lability
<u>Degradability:</u>	The product is expected to be slowly biodegradable.
12.3. Bioaccumulative poten	tial
Bioaccumulative potential:	No data available on bioaccumulation.
<u>12.4. Mobility in soil</u>	
<u>Mobility:</u>	The product adsorbs to soil particles. The product is non-volatile.
12.5. Results of PBT and vP	vB assessment
<u>PBT/vPvB:</u>	No information available.
12.6.Information on other I	nazards
Endocrine disrupting properties:	The product does not contain any substance identified as having endocrine disrupting properties.
12.7. Other adverse effects	
Other adverse effects:	No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

Waste from residues:	EWC-code: 13 02 05
Contaminated packaging:	Dispose of contaminated packings as residue.
Empty packaging:	The packaging should be collected for reuse.

Product name:	Outboard Gear Oil EP 90	Page:	9/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 14: TRANSPORT INFORMATION

The product is not covered by international regulation on the transport of dangerous goods (IMDG, IATA, ADR/ADN/RID).

14.1. UN number

UN-No:

14.2. UN proper shipping name

Proper Shipping Name:

14.3. Transport hazard class(es)

<u>Class:</u> <u>14.4. Packing group</u> PG:

14.5. Environmental hazards

Marine pollutant:

Environmentally Hazardous substance:

14.6. Special precautions for user

Special precautions:

None known.

14.7. Maritime transport in bulk according to IMO Instruments

Transport in bulk: Not relevant.

Product name:	Outboard Gear Oil EP 90	Page:	10/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions:	DK - PR-nr.: 1795432
EU regulation:	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, with amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, with amendments. Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative limit values by implementing Council Directive 98/24/EC on the protection of use stablishing a first list of indicative limit values by implementing Council Directive 98/24/EC on the protection of workers from the risks related to exposure to chemical, physical and biological agents at work, with amendments. Directive 2004/37/EC of the European Parliament and of the Council of 29 April 2004 on the protection of workers from the risks related to exposure to carcinogens or mutagens at work, with amendments. Directive 2009/148/EC of the European Parliament and of the Council of 30 November 2009 on the protection of workers from the risks related to exposure to asbestos at work, with amendments.

15.2. Chemical Safety Assessment

CSA status:

No chemical safety assessment has been carried out.

Product name:	Outboard Gear Oil EP 90	Page:	11/11
Supersedes date:	2020-08-06	Last revised date:	2024-03-25
Product No.:	61018	SDS-ID:	EU-EN/4.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

Handling of used oils:

Protect health - avoid prolonged and repeated skin contact. Wash with soap and water. Protect the environment - do not pollute drains, water courses or the soil. Contact your local authority for any used oil disposal instructions.

The following sections contain revisions or new statements: 1, 2, 3, 4, 8, 9, 10, 11, 12, 13, 14, 15, 16.

Abbreviations and acronyms

used in the safety data sheet:	CSA = Chemical Safety Assessment.
	EWC = European Waste Catalogue.
	M(ac) = M-factor acute toxicity.
	M(chr) = M-factor chronic toxicity.
	PBT = Persistent, Bioaccumulative and Toxic.
	SCL = Specific Concentration Limit.
	vPvB = very Persistent and very Bioaccumulative.

Wording of H-statements:

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.