

Product data sheet

SUPERLA® 40

Paraffinum Perliquidum, Light Liquid Paraffin

<u>Parameter</u>	<u>Methods</u>	<u>Dimension</u>	<u>Values</u>
Colour Saybolt	ASTM D156	-	min. +30
Density 15°C	DIN EN ISO 3675	g/cm ³	0,830 - 0,870
Rel. Density 20/20	Ph. Eur. 2.2.5	-	0,810 - 0,875
Flashpoint COC	ASTM D92	°C	min. 165
Pourpoint	ASTM D97	°C	max. -6
Kin. Viscosity 40°C	ASTM D445	mm ² /s	14,5 - 17,5
Kin. Viscosity 100°C	ASTM D445	mm ² /s	typ. 3,5
Dyn. Viscosity 20°C	Ph. Eur. 2.2.9	mPas	25 - 80
Typical Carbon Type Distribution	ASTM D2140		
C _A		% w/w	0
C _N		% w/w	35
C _P		% w/w	65
European Pharmacopoeia (PH.EUR.) latest version			pass
United States Pharmacopoeia (USP) / National Formulary (NF) latest version			pass
FDA §178.3620(a)			pass

This product data sheet and the information within were assembled and checked with utmost care and are to be regarded as accurate as of the date of issue. Nevertheless, FUCHS Schmierstoffe GmbH takes no responsibility or warrant for its timeliness, completeness, quality or correctness. This product data sheet is for information only and does not warrant any particular product properties. It is the user's obligation to check the products and use them safely as well as to comply with all applicable laws and regulations. FUCHS Schmierstoffe GmbH shall not be responsible for any damage or injury in particular resulting from use, other than the stated use of the material, from any failure to abide to recommendations, or from any dangers inherent in the nature of the material. In addition, the most recent version of our General Conditions of Sale and Delivery will apply.

Revision: 04.2021



Nonfood Compounds
Program Listed (H1, HX-1, 3H)

FUCHS LUBRICANTS GERMANY GmbH
Friesenheimer Straße 19
68169 Mannheim
Business Unit PARAFIUID
Tel +49 40 63 704 00
Info-parafluid@fuchs.com

