

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : ANDEROL 555

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Lubricant

Recommended restrictions  
on use : Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

:

Company:

Manufacturer  
Anderol Specialty Lubricants  
Groot Egtenrayseweg 23  
5928 PA Venlo  
Netherlands

Telephone : +31-77 396 0340

Supplier  
LANXESS Solutions UK Ltd.  
Tenax Road, Trafford Park  
Manchester  
United Kingdom  
M17 1WT

Customer Service:  
Prepared by

+44 161 875 3800  
Product Safety Department  
(US) +1 866-430-2775

Further information for the safety data sheet : MSDSRe-  
quest@lanxess.com

#### 1.4 Emergency telephone number

Emergency telephone  
number: +44 (0) 1235 239 670 (NCEC)

For additional emergency telephone numbers see section 16 of  
the Safety Data Sheet.

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

**Classification (REGULATION (EC) No 1272/2008)**

Long-term (chronic) aquatic hazard, Category 3      H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

**Labelling (REGULATION (EC) No 1272/2008)**

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.  
**Disposal:**  
P501 Dispose of contents/ container to an approved waste disposal plant.

**Additional Labelling**

EUH208 Contains N-1-naphthylaniline. May produce an allergic reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
N-1-naphthylaniline	90-30-2 201-983-0 01-2119488704-27-xxxx	Acute Tox. 4; H302 Skin Sens. 1B; H317 STOT RE 2; H373 Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0.25 - < 1

For explanation of abbreviations see section 16.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing  
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
- If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion.  
If symptoms persist, call a physician.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.
- In case of eye contact : Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : None known.

#### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : For specialist advice physicians should contact the Poisons Information Service.
- 

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire-fighting : Burning produces noxious and toxic fumes.

#### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

#### 6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.  
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of work-day.

Dust explosion class : No data available

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Keep in a dry place. Store at room temperature.

Storage period : 5 y

Further information on storage stability : Keep in a dry place.

#### 7.3 Specific end use(s)

Specific use(s) : Raw material for industry

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Contains no substances with occupational exposure limit values.

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
N-1-naphthylaniline	Workers	Inhalation	Long-term systemic effects	0.18 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	44 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	0.05 mg/kg
	Workers	Dermal	Acute systemic effects	6.67 mg/kg
	General exposures	Inhalation	Long-term systemic effects	0.044 mg/m <sup>3</sup>
	General exposures	Inhalation	Acute systemic effects	33 mg/m <sup>3</sup>
	General exposures	Dermal	Long-term systemic effects	0.03 mg/kg
	General exposures	Dermal	Long-term systemic effects	3.33 mg/kg
	General exposures	Ingestion	Long-term systemic effects	0.03 mg/kg
	General exposures	Ingestion	Acute systemic effects	8 mg/kg

#### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
N-1-naphthylaniline	Fresh water	0.0002 mg/l
	Marine water	0.00002 mg/l
	Fresh water sediment	0.0344 mg/kg
	Marine sediment	0.00344 mg/kg
	Soil	0.0068 mg/kg
	STP	100 mg/l

#### 8.2 Exposure controls

##### Engineering measures

Effective exhaust ventilation system

Ensure that eyewash stations and safety showers are close to the workstation location.

##### Personal protective equipment

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

Hand protection

Remarks

: Polyvinyl alcohol or nitrile- butyl-rubber gloves The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Before removing gloves clean them with soap and water.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Breathing apparatus needed only when aerosol or mist is formed.  
Respirator with filter for organic vapour

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Appearance	:	oily
Colour	:	light yellow
Odour	:	ester-like
Odour Threshold	:	Not relevant
pH	:	Not applicable
Pour point	:	-33 °C
Boiling point/boiling range	:	No data available
Flash point	:	250 °C
Evaporation rate	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	0.956 (15 °C)
Density	:	0.957 g/cm <sup>3</sup> (15 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	93.5 mPa.s (40 °C)
Viscosity, kinematic	:	103 mm <sup>2</sup> /s (40 °C)

### 9.2 Other information

Self-Accelerating decomposition temperature (SADT)	:	Method: No information available.
Flammability (liquids)	:	Not classified as supporting combustion according to the transport regulations.
Oxidizing potential	:	No information available.
Molecular weight	:	No data available
Dust explosion class	:	No data available
Metal corrosion rate	:	Not corrosive to metals

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Stable under recommended storage conditions.  
No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if used as directed.

### 10.4 Conditions to avoid

Conditions to avoid : Contamination

### 10.5 Incompatible materials

Materials to avoid : Contamination

### 10.6 Hazardous decomposition products

Hazardous decomposition products : No decomposition if stored normally.

**ANDEROL 555**

Version      Revision Date:      SDS Number:      Date of last issue: 13.02.2020  
1.19          05.10.2020          000000007152      Date of first issue: 07.03.2014

---

**SECTION 11: Toxicological information**

**11.1 Information on toxicological effects**

Information on likely routes of exposure

Inhalation  
Eye contact  
Skin contact  
Skin Absorption

**Acute toxicity**

**Product:**

Acute inhalation toxicity : Remarks: Not classified due to lack of data.

**Components:**

**N-1-naphthylaniline:**

Acute oral toxicity : LD50 (Rat): 1,625 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5,000 mg/kg

**Skin corrosion/irritation**

**Components:**

**N-1-naphthylaniline:**

Species : Rabbit  
Method : Draize Test  
Result : No skin irritation

**Serious eye damage/eye irritation**

**Components:**

**N-1-naphthylaniline:**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

**Respiratory or skin sensitisation**

**Components:**

**N-1-naphthylaniline:**

Test Type : Maximisation Test  
Species : Guinea pig  
Result : Probability or evidence of low to moderate skin sensitisation rate in humans



**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

---

**Germ cell mutagenicity**

**Product:**

Germ cell mutagenicity- Assessment : Not classified due to lack of data.

**Components:**

**N-1-naphthylaniline:**

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Result: negative

Test Type: Chinese Hamster Ovary (CHO)  
Metabolic activation: with and without metabolic activation  
Result: negative

Genotoxicity in vivo : Test Type: in vivo assay  
Species: Mouse (male)  
Result: negative

Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects., Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

**Carcinogenicity**

**Product:**

Carcinogenicity - Assessment : Not classified due to lack of data.

**Components:**

**N-1-naphthylaniline:**

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

**Reproductive toxicity**

**Product:**

Reproductive toxicity - Assessment : Not classified due to lack of data.

**STOT - single exposure**

**Product:**

Assessment : Not classified due to lack of data.

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

---

**STOT - repeated exposure**

**Product:**

Assessment : Not classified due to lack of data.

**Components:**

**N-1-naphthylaniline:**

Exposure routes : Oral  
Target Organs : Liver, Kidney  
Assessment : May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

**Product:**

No aspiration toxicity classification

**Further information**

**Product:**

Remarks : No data is available on the product itself.

---

**SECTION 12: Ecological information**

**12.1 Toxicity**

**Product:**

Toxicity to fish : Remarks: No data available

**Components:**

**N-1-naphthylaniline:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.44 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Analytical monitoring: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.68 mg/l  
Exposure time: 48 h  
Test Type: semi-static test  
Analytical monitoring: yes

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Protozoa): 2 mg/l  
Exposure time: 48 h  
EC50 (Bacteria): > 10,000 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

Exposure time: 3 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.02 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Analytical monitoring: yes

M-Factor (Chronic aquatic toxicity) : 1

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Result: No data available

#### Components:

##### **N-1-naphthylaniline:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Concentration: 100 mg/l  
Result: According to the results of tests of biodegradability this product is not readily biodegradable.  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301  
GLP: yes

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: No data available

#### Components:

##### **N-1-naphthylaniline:**

Bioaccumulation : Species: Cyprinus carpio (Carp)  
Exposure time: 56 d  
Temperature: 25 °C  
Concentration: 0.1 mg/l  
Bioconcentration factor (BCF): 427 - 2,730

Partition coefficient: n-octanol/water : log Pow: 4.28

### 12.4 Mobility in soil

#### Product:

Mobility : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

**Product:**

Additional ecological information : The product itself has not been tested. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

---

## SECTION 14: Transport information

### 14.1 UN number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

Not regulated as a dangerous good

### 14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.  
Not applicable

#### The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- NZIoC : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TCSI : On the inventory, or in compliance with the inventory
- US.TSCA : All substances listed as active on the TSCA inventory

### 15.2 Chemical safety assessment

No information available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

### SECTION 16: Other information

#### Full text of H-Statements

H302 : Harmful if swallowed.  
H317 : May cause an allergic skin reaction.  
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.  
H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Skin Sens. : Skin sensitisation  
STOT RE : Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### Further information

**Classification of the mixture:**

**Classification procedure:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Energizing Chemistry

## ANDEROL 555

Version	Revision Date:	SDS Number:	Date of last issue: 13.02.2020
1.19	05.10.2020	000000007152	Date of first issue: 07.03.2014

---

Aquatic Chronic 3

H412

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DK / EN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

## Annex: Exposure Scenarios

### Table of Contents

Number	Title
ES 1	Formulation or re-packing; Formulation of preparations; Lubricants, greases, release products; (N-1-naphthylaniline, CAS: 90-30-2).
ES 2	Use at industrial sites; General exposures; Lubricants, greases, release products; Engine lubricant service; (N-1-naphthylaniline, CAS: 90-30-2).
ES 3	Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; In-door use; (N-1-naphthylaniline, CAS: 90-30-2).
ES 4	Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; Out-door use; (N-1-naphthylaniline, CAS: 90-30-2).
ES 5	Use at industrial sites; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; (N-1-naphthylaniline, CAS: 90-30-2).
ES 6	Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Indoor use.
ES 7	Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Out-door use.
ES 8	Use at industrial sites; Lubricants, greases, release products; Treatment by heating; (open systems).



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 1: Formulation or re-packing; Formulation of preparations; Lubricants, greases, release products; (N-1-naphthylaniline, CAS: 90-30-2).**

### 1.1. Title section

<b>Exposure Scenario name</b>	: Formulation of preparations, Lubricants, greases, release products
<b>Structured Short Title</b>	: Formulation or re-packing; Formulation of preparations; Lubricants, greases, release products; (N-1-naphthylaniline, CAS: 90-30-2).
<b>Substance</b>	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx

Environment		
CS 1	Formulation of preparations	ERC2
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Use in closed batch process (synthesis or formulation)	PROC3
CS 5	Use in batch and other process (synthesis) where opportunity for exposure arises	PROC4
CS 6	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)	PROC5
CS 7	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities	PROC8a
CS 8	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC9
CS 10	Use as laboratory reagent	PROC15

### 1.2. Conditions of use affecting exposure

#### 1.2.1. Control of environmental exposure: Formulation of preparations (ERC2)

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Daily amount per site	: 233.33 kg
Annual amount per site	: 70000 kg
Release type	: Intermittent use/release
Emission days	: 300
<b>Technical and organisational conditions and measures</b>	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.005 %	
<b>Emission or Release Factor: Water</b> Worst case assumption 0 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0 %	

**1.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)**

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Liquid substance
Vapour pressure	: < 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 480 min

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Use frequency	: Covers daily exposures up to 8 hours (unless stated differently). 5 days/week
<b>Technical and organisational conditions and measures</b>	
Handle substance within a closed system. Provide a basic standard of general ventilation (1 to 3 air changes per hour).	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
<=27%	
Physical form of product	: Liquid substance
Vapour pressure	: < 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 480 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently). 5 days/week
<b>Technical and organisational conditions and measures</b>	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Handle substance within a closed system. Use only in area provided with appropriate exhaust ventilation. Inhalation - minimum efficiency of 90 %	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.4. Control of worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)

<b>Product (article) characteristics</b>	
<=27%	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently). 5 days/week
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.5. Control of worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC4)

<b>Product (article) characteristics</b>	
<=27%	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Physical form of product	: Liquid mixture
Vapour pressure	: < 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
Use frequency	: 5 days/week
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.6. Control of worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) (PROC5)

<b>Product (article) characteristics</b>	
Limit the substance content in the product to 10 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: < 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
Use frequency	: 5 days/week
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.7. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Solid, low dustiness
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 60 min
Use frequency	: 5 days/week
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 1.2.8. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Solid, low dustiness
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 60 min
Use frequency	: 5 days/week
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 95 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.9. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

<b>Product (article) characteristics</b>	
<=27%	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 1.2.10. Control of worker exposure: Use as laboratory reagent (PROC15)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 100 % (unless stated differently).	
Physical form of product	: Solid, low dustiness
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur. Inhalation - minimum efficiency of 90 %	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	



**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**1.3. Exposure estimation and reference to its source**

**1.3.1. Environmental release and exposure: Formulation of preparations (ERC2)**

Protection Target	Exposure estimate	RCR
Fresh water	0.000007 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EASY TRA v4.1)	< 0.001

**1.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m <sup>3</sup> (EASY TRA v4.1)	0.508
dermal	systemic	long-term	0.002 mg/kg bw/day (EASY TRA v4.1)	0.034

**1.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.054
dermal	systemic	long-term	0.019 mg/kg bw/day (ECETOC TRA worker v3)	0.37

**1.3.4. Worker exposure: Use in closed batch process (synthesis or formulation) (PROC3)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
----------------	---------------	--------------------	-------------------	-----

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version  
1.19

Revision Date:  
05.10.2020

SDS Number:  
000000007152

Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

		tor	mate	
inhalative	systemic	long-term	0.091 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.508
dermal	systemic	long-term	0.009 mg/kg bw/day (ECETOC TRA worker v3)	0.185

### 1.3.5. Worker exposure: Use in batch and other process (synthesis) where opportunity for exposure arises (PROC4)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.022 mg/kg bw/day (ECETOC TRA worker v3)	0.444

### 1.3.6. Worker exposure: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact) (PROC5)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.033 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.183
dermal	systemic	long-term	0.016 mg/kg bw/day (ECETOC TRA worker v3)	0.329

### 1.3.7. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m <sup>3</sup> (EASY TRA v4.1)	0.056
dermal	systemic	long-term	0.017 mg/kg bw/day (RISKOFDERM v2.1)	0.336

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 1.3.8. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.001 mg/m <sup>3</sup> (EASY TRA v4.1)	0.006
dermal	systemic	long-term	0.017 mg/kg bw/day (RISKOFDERM v2.1)	0.336

### 1.3.9. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.022 mg/kg bw/day (ECETOC TRA worker v3)	0.444

### 1.3.10. Worker exposure: Use as laboratory reagent (PROC15)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.006 mg/m <sup>3</sup> (EASY TRA v4.1)	0.033
dermal	systemic	long-term	0.010 mg/kg bw/day (EASY TRA v4.1)	0.206

## 1.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 2: Use at industrial sites; General exposures; Lubricants, greases, release products; Engine lubricant service; (N-1-naphthylaniline, CAS: 90-30-2).**

### 2.1. Title section

<b>Exposure Scenario name</b>	: General exposures, Lubricants, greases, release products, Engine lubricant service
<b>Structured Short Title</b>	: Use at industrial sites; General exposures; Lubricants, greases, release products; Engine lubricant service; (N-1-naphthylaniline, CAS: 90-30-2).
<b>Substance</b>	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx

Environment		
<b>CS 1</b>	<b>Industrial use of processing aids in processes and products, not becoming part of articles</b>	ERC4
Worker		
<b>CS 2</b>	<b>Use in closed process, no likelihood of exposure</b>	PROC1
<b>CS 3</b>	<b>Use in closed, continuous process with occasional controlled exposure</b>	PROC2
<b>CS 4</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</b>	PROC8b
<b>CS 5</b>	<b>Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</b>	PROC9

### 2.2. Conditions of use affecting exposure

#### 2.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 100 kg
Annual amount per site	: 30000 kg
Release type	: Intermittent use/release
Emission days	: 300

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Technical and organisational conditions and measures</b>	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.005 %	
<b>Emission or Release Factor: Water</b> Worst case assumption 0 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0 %	

**2.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)**

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 2.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 2.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 2.2.5. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Conditions and measures related to personal protection, hygiene and health evaluation	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 2.3. Exposure estimation and reference to its source

#### 2.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	0.0000012 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EASY TRA v4.1)	< 0.001

#### 2.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.018 mg/m <sup>3</sup> (EASY TRA v4.1)	0.102
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 2.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA worker v3)	0.069

### 2.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.110 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.609
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

### 2.3.5. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.007 mg/kg bw/day (ECETOC TRA worker v3)	0.137

## 2.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 3: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; In-door use; (N-1-naphthylaniline, CAS: 90-30-2).**

### 3.1. Title section

<b>Exposure Scenario name</b>	: General exposures, Lubricants, greases, release products, Engine lubricant service, Indoor use
<b>Structured Short Title</b>	: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; In-door use; (N-1-naphthylaniline, CAS: 90-30-2).
<b>Substance</b>	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx

Environment		
<b>CS 1</b>	<b>Wide dispersive indoor use of substances in closed systems</b>	ERC9a
Worker		
<b>CS 2</b>	<b>Use in closed process, no likelihood of exposure</b>	PROC1
<b>CS 3</b>	<b>Use in closed, continuous process with occasional controlled exposure</b>	PROC2
<b>CS 4</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</b>	PROC8a
<b>CS 5</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</b>	PROC8b
<b>CS 6</b>	<b>Heat and pressure transfer fluids in dispersive, professional use but closed systems</b>	PROC20

### 3.2. Conditions of use affecting exposure

#### 3.2.1. Control of environmental exposure: Wide dispersive indoor use of substances in closed systems (ERC9a)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: 0.002 kg
Annual amount for wide disperse	: 15000 kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

uses	
Release type	: Intermittent use/release
Emission days	: 365
<b>Technical and organisational conditions and measures</b>	
Product must not be released into water without pre-treatment.	
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m3/d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.01 %	
<b>Emission or Release Factor: Water</b> Worst case assumption 0.05 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0.1 %	

### 3.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 3.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 3.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 3.2.5. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 3.2.6. Control of worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Provide extraction ventilation at points where emissions occur.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Engerizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 3.3. Exposure estimation and reference to its source

#### 3.3.1. Environmental release and exposure: Wide dispersive indoor use of substances in closed systems (ERC9a)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.034
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.035
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	0.0000005 mg/L (EASY TRA v4.1)	< 0.001

#### 3.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.009 mg/m <sup>3</sup> (EASY TRA v4.1)	0.051
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

#### 3.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m <sup>3</sup> (EASY TRA v4.1)	0.508
dermal	systemic	long-term	0.014 mg/kg bw/day (EASY TRA v4.1)	0.274

#### 3.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

### 3.3.5. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

### 3.3.6. Worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m <sup>3</sup> (EASY TRA v4.1)	0.305
dermal	systemic	long-term	0.017 mg/kg bw/day (EASY TRA v4.1)	0.343

### 3.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 4: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; Out-door use; (N-1-naphthylaniline, CAS: 90-30-2).**

### 4.1. Title section

<b>Exposure Scenario name</b>	: General exposures, Lubricants, greases, release products, Engine lubricant service, Outdoor use
<b>Structured Short Title</b>	: Widespread use by professional workers; General exposures; Lubricants, greases, release products; Engine lubricant service; Out-door use; (N-1-naphthylaniline, CAS: 90-30-2).
<b>Substance</b>	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx

Environment		
<b>CS 1</b>	<b>Wide dispersive outdoor use of substances in closed systems</b>	ERC9b
Worker		
<b>CS 2</b>	<b>Use in closed process, no likelihood of exposure</b>	PROC1
<b>CS 3</b>	<b>Use in closed, continuous process with occasional controlled exposure</b>	PROC2
<b>CS 4</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</b>	PROC8a
<b>CS 5</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</b>	PROC8b
<b>CS 6</b>	<b>Heat and pressure transfer fluids in dispersive, professional use but closed systems</b>	PROC20

### 4.2. Conditions of use affecting exposure

#### 4.2.1. Control of environmental exposure: Wide dispersive outdoor use of substances in closed systems (ERC9b)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount for wide dispersive uses	: 0.002 kg
Annual amount for wide disperse	: 15000 kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

uses	
Release type	: Intermittent use/release
Emission days	: 365
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: none
STP effluent	: 2,000 m3/d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.01 %	
<b>Emission or Release Factor: Water</b> Worst case assumption 0.05 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0.1 %	

### 4.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training.  
Dermal - minimum efficiency of 90 %

### Other conditions affecting workers exposure

Body parts exposed : 240 cm<sup>2</sup>

Indoor or outdoor use : Outdoor

### 4.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

#### Product (article) characteristics

Covers percentage substance in the product up to 1 %.

Physical form of product : Liquid mixture

#### Amount used (or contained in articles), frequency and duration of use/exposure

Duration : Exposure duration > 240 min

Use frequency : Covers daily exposures up to 8 hours (unless stated differently).

#### Technical and organisational conditions and measures

General standard operating procedures to control routine activities  
Ensure operatives are trained to minimise exposures.

#### Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374.  
Dermal - minimum efficiency of 90 %

### Other conditions affecting workers exposure

Body parts exposed : Palms of both hands (480 cm<sup>2</sup>)

Indoor or outdoor use : Outdoor

### 4.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

#### Product (article) characteristics

Covers percentage substance in the product up to 1 %.

Physical form of product : Liquid mixture

#### Amount used (or contained in articles), frequency and duration of use/exposure

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Duration	:	Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>		
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.		
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>		
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %		
<b>Other conditions affecting workers exposure</b>		
Body parts exposed	:	960 cm <sup>2</sup>
Indoor or outdoor use	:	Outdoor

#### 4.2.5. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

<b>Product (article) characteristics</b>		
Covers percentage substance in the product up to 1 %.		
Physical form of product	:	Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>		
Duration	:	Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>		
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.		
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>		
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %		
<b>Other conditions affecting workers exposure</b>		
Body parts exposed	:	960 cm <sup>2</sup>
Indoor or outdoor use	:	Outdoor

#### 4.2.6. Control of worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Outdoor

### 4.3. Exposure estimation and reference to its source

#### 4.3.1. Environmental release and exposure: Wide dispersive outdoor use of substances in closed systems (ERC9b)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.034
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.035
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001

#### 4.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version  
1.19

Revision Date:  
05.10.2020

SDS Number:  
000000007152

Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.006 mg/m <sup>3</sup> (EASY TRA v4.1)	0.036
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

### 4.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.064 mg/m <sup>3</sup> (EASY TRA v4.1)	0.355
dermal	systemic	long-term	0.013 mg/kg bw/day (EASY TRA v4.1)	0.274

### 4.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.038 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.213
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

### 4.3.5. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.038 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.213
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**4.3.6. Worker exposure: Heat and pressure transfer fluids in dispersive, professional use but closed systems (PROC20)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.038 mg/m <sup>3</sup> (EASY TRA v4.1)	0.213
dermal	systemic	long-term	0.017 mg/kg bw/day (EASY TRA v4.1)	0.343

**4.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 5: Use at industrial sites; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; (N-1-naphthylaniline, CAS: 90-30-2).**

### 5.1. Title section

<b>Exposure Scenario name</b>	: General exposures (open systems), Use of lubricants and greases, Corrosion inhibitors, Rolling, Brushing, Dipping, Spraying
<b>Structured Short Title</b>	: Use at industrial sites; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; (N-1-naphthylaniline, CAS: 90-30-2).
<b>Substance</b>	: N-1-naphthylaniline EC-No.: 201-983-0 Registration number: 01-2119488704-27-xxxx

Environment		
CS 1	Industrial use of processing aids in processes and products, not becoming part of articles	ERC4
Worker		
CS 2	Use in closed process, no likelihood of exposure	PROC1
CS 3	Use in closed, continuous process with occasional controlled exposure	PROC2
CS 4	Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities	PROC8b
CS 5	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)	PROC9
CS 6	Roller application or brushing	PROC10
CS 7	Treatment of articles by dipping and pouring	PROC13

### 5.2. Conditions of use affecting exposure

#### 5.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 100 kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Annual amount per site	: 30000 kg
Release type	: Intermittent use/release
Emission days	: 300
<b>Technical and organisational conditions and measures</b>	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Default industrial size
STP effluent	: 2,000 m3/d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.005 %	
<b>Emission or Release Factor: Water</b> Worst case assumption 0 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0 %	

### 5.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 5.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Assumes a good basic standard of occupational hygiene is implemented

### 5.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 5.2.5. Control of worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 60 min
<b>Technical and organisational conditions and measures</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 5.2.6. Control of worker exposure: Roller application or brushing (PROC10)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
<b>Technical and organisational conditions and measures</b>	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
Use only in area provided with appropriate exhaust ventilation. Dermal - minimum efficiency of 90 %	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**5.2.7. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)**

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls. Dermal - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

**5.3. Exposure estimation and reference to its source**

**5.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)**

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight	< 0.001

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

	(EASY TRA v4.1)	
Soil	0.0000012 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EASY TRA v4.1)	< 0.001

### 5.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.018 mg/m <sup>3</sup> (EASY TRA v4.1)	0.102
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

### 5.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA worker v3)	0.069

### 5.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.110 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.609
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

### 5.3.5. Worker exposure: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) (PROC9)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
----------------	---------------	--------------------	-------------------	-----

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

		tor	mate	
inhalative	systemic	long-term	0.037 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.203
dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA worker v3)	0.069

### 5.3.6. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.009 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.051
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA worker v3)	0.274

### 5.3.7. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.541
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA worker v3)	0.274

### 5.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 6: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Indoor use.**

**6.1. Title section**

<b>Exposure Scenario name</b>	: General exposures (open systems), Use of lubricants and greases, Corrosion inhibitors, Rolling, Brushing, Dipping, Spraying, Indoor use
<b>Structured Short Title</b>	: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Indoor use.
<b>Substance</b>	: N-1-naphthylaniline EC-No.: 201-983-0 Registration number: 01-2119488704-27-xxxx

Environment		
<b>CS 1</b>	<b>Wide dispersive indoor use of processing aids in open systems</b>	ERC8a
Worker		
<b>CS 2</b>	<b>Use in closed process, no likelihood of exposure</b>	PROC1
<b>CS 3</b>	<b>Use in closed, continuous process with occasional controlled exposure</b>	PROC2
<b>CS 4</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities</b>	PROC8a
<b>CS 5</b>	<b>Roller application or brushing</b>	PROC10
<b>CS 6</b>	<b>Treatment of articles by dipping and pouring</b>	PROC13

**6.2. Conditions of use affecting exposure**

**6.2.1. Control of environmental exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a)**

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 0.822 kg
Annual amount for wide disperse uses	: 6000 kg



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Release type	:	Intermittent use/release
Emission days	:	365
<b>Technical and organisational conditions and measures</b>		
Product must not be released into water without pre-treatment.		
Soil emission controls are not applicable as there is no direct release to soil.		
<b>Conditions and measures related to sewage treatment plant</b>		
STP type	:	Municipal sewage treatment plant
STP effluent	:	2,000 m <sup>3</sup> /d
<b>Conditions and measures related to treatment of waste (including article waste)</b>		
Waste treatment	:	Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>		
Receiving surface water flow	:	18,000 m <sup>3</sup> /d
Local freshwater dilution factor	:	10
Local marine water dilution factor	:	100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.010 %		
<b>Emission or Release Factor: Water</b> Worst case assumption 0.050 %		
<b>Emission or Release Factor: Soil</b> Worst case assumption 0.100 %		

### 6.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

<b>Product (article) characteristics</b>		
Covers percentage substance in the product up to 1 %.		
Physical form of product	:	Liquid mixture
Vapour pressure	:	> 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>		
Duration	:	Exposure duration > 240 min
Use frequency	:	Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>		

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Handle substance within a closed system.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 6.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 6.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear suitable gloves tested to EN374. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 6.2.5. Control of worker exposure: Roller application or brushing (PROC10)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Application rate	: 0.2 L/min
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Ensure that direction of application is only downward.	

### 6.2.6. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**6.3. Exposure estimation and reference to its source**

**6.3.1. Environmental release and exposure: Wide dispersive indoor use of processing aids in open systems (ERC8a)**

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Sewage treatment plant	0.0000002 mg/L (EASY TRA v4.1)	< 0.001

**6.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.009 mg/m <sup>3</sup> (EASY TRA v4.1)	0.051
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

**6.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m <sup>3</sup> (EASY TRA v4.1)	0.508
dermal	systemic	long-term	0.014 mg/kg bw/day (EASY TRA v4.1)	0.274

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

### 6.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities (PROC8a)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.055 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.305
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA worker v3)	0.165

### 6.3.5. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m <sup>3</sup> (ART)	0.054
dermal	systemic	long-term	0.038 mg/kg bw/day (RISKOFDERM v2.1)	0.76

### 6.3.6. Worker exposure: Treatment of articles by dipping and pouring (PROC13)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.091 mg/m <sup>3</sup> (ECETOC TRA worker v3)	0.508
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA worker v3)	0.274

## 6.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 7: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Outdoor use.**

**7.1. Title section**

<b>Exposure Scenario name</b>	: General exposures (open systems), Use of lubricants and greases, Corrosion inhibitors, Rolling, Brushing, Dipping, Spraying, Outdoor use
<b>Structured Short Title</b>	: Widespread use by professional workers; General exposures (open systems); Lubricants, greases, release products; Corrosion inhibitors; Dipping; Spraying; Rolling, Brushing; Outdoor use.
<b>Substance</b>	: N-1-naphthylaniline EC-No.: 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx

<b>Environment</b>		
<b>CS 1</b>	<b>Wide dispersive outdoor use of processing aids in open systems</b>	ERC8d
<b>Worker</b>		
<b>CS 2</b>	<b>Use in closed process, no likelihood of exposure</b>	PROC1
<b>CS 3</b>	<b>Use in closed, continuous process with occasional controlled exposure</b>	PROC2
<b>CS 4</b>	<b>Roller application or brushing</b>	PROC10

**7.2. Conditions of use affecting exposure**

**7.2.1. Control of environmental exposure: Wide dispersive outdoor use of processing aids in open systems (ERC8d)**

<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Daily amount per site	: 0.822 kg
Annual amount for wide disperse uses	: 6000 kg
Release type	: Intermittent use/release
Emission days	: 365

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Technical and organisational conditions and measures</b>	
Product must not be released into water without pre-treatment.	
Soil emission controls are not applicable as there is no direct release to soil.	
<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: none
STP effluent	: 2,000 m3/d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m3/d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.010 %	
<b>Emission or Release Factor: Water</b> Worst case assumption 0.050 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0.100 %	

**7.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)**

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Handle substance within a closed system.	
General standard operating procedures to control routine activities	



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Outdoor
Assumes a good basic standard of occupational hygiene is implemented	

### 7.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Outdoor
Assumes a good basic standard of occupational hygiene is implemented	

### 7.2.4. Control of worker exposure: Roller application or brushing (PROC10)

<b>Product (article) characteristics</b>
--

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Covers percentage substance in the product up to 1 %.	
Physical form of product	: Liquid mixture
Vapour pressure	: > 10 hPa
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Application rate	: 0.2 L/min
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
General standard operating procedures to control routine activities Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with 'basic' employee training. Dermal - minimum efficiency of 90 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Outdoor
Assumes a good basic standard of occupational hygiene is implemented	
<b>Additional good practice advice. Obligations according to Article 37(4) of REACH do not apply</b>	
Ensure that direction of application is only downward.	

### 7.3. Exposure estimation and reference to its source

#### 7.3.1. Environmental release and exposure: Wide dispersive outdoor use of processing aids in open systems (ERC8d)

Protection Target	Exposure estimate	RCR
Fresh water	0.0000067 mg/L (EASY TRA v4.1)	0.033
Marine water	0.0000007 mg/L (EASY TRA v4.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EASY TRA v4.1)	< 0.001
Marine sediment	0.0000027 mg/kg dry weight	< 0.001

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

	(EASY TRA v4.1)	
Soil	< 0.0000001 mg/kg dry weight (EASY TRA v4.1)	< 0.001

### 7.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.006 mg/m <sup>3</sup> (EASY TRA v4.1)	0.036
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

### 7.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.064 mg/m <sup>3</sup> (EASY TRA v4.1)	0.355
dermal	systemic	long-term	0.014 mg/kg bw/day (EASY TRA v4.1)	0.274

### 7.3.4. Worker exposure: Roller application or brushing (PROC10)

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.01 mg/m <sup>3</sup> (ART)	0.054
dermal	systemic	long-term	0.038 mg/kg bw/day (RISKOFDERM v2.1)	0.76

## 7.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

**ES 8: Use at industrial sites; Lubricants, greases, release products; Treatment by heating; (open systems).**

**8.1. Title section**

<b>Exposure Scenario name</b>	: Treatment by heating, Lubricants, greases, release products, (open systems)
<b>Structured Short Title</b>	: Use at industrial sites; Lubricants, greases, release products; Treatment by heating; (open systems).
<b>Substance</b>	: N-1-naphthylaniline <u>EC-No.:</u> 201-983-0 <u>Registration number:</u> 01-2119488704-27-xxxx

Environment		
<b>CS 1</b>	<b>Industrial use of processing aids in processes and products, not becoming part of articles</b>	ERC4
Worker		
<b>CS 2</b>	<b>Use in closed process, no likelihood of exposure</b>	PROC1
<b>CS 3</b>	<b>Use in closed, continuous process with occasional controlled exposure</b>	PROC2
<b>CS 4</b>	<b>Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities</b>	PROC8b
<b>CS 5</b>	<b>Treatment of articles by dipping and pouring</b>	PROC13

**8.2. Conditions of use affecting exposure**

**8.2.1. Control of environmental exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)**

Amount used (or contained in articles), frequency and duration of use/exposure	
Daily amount per site	: 20 kg
Annual amount per site	: 6000 kg
Release type	: Intermittent use/release
Emission days	: 300
Technical and organisational conditions and measures	
Product must not be released into water without pre-treatment.	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Conditions and measures related to sewage treatment plant</b>	
STP type	: Municipal sewage treatment plant
STP effluent	: 2,000 m <sup>3</sup> /d
<b>Conditions and measures related to treatment of waste (including article waste)</b>	
Waste treatment	: Can be incinerated, when in compliance with local regulations.
<b>Other conditions affecting environmental exposure</b>	
Receiving surface water flow	: 18,000 m <sup>3</sup> /d
Local freshwater dilution factor	: 10
Local marine water dilution factor	: 100
<b>Emission or Release Factor: Air</b> Worst case assumption 0.005 %	
<b>Emission or Release Factor: Water</b> Worst case assumption < 0.001 %	
<b>Emission or Release Factor: Soil</b> Worst case assumption 0 %	

### 8.2.2. Control of worker exposure: Use in closed process, no likelihood of exposure (PROC1)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Body parts exposed	: 240 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 8.2.3. Control of worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with specific activity training. Dermal - minimum efficiency of 95 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	

### 8.2.4. Control of worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration < 240 min

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

# LANXESS

Energizing Chemistry

## ANDEROL 555

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

<b>Technical and organisational conditions and measures</b>	
Ensure adequate ventilation, especially in confined areas.	
Ensure operatives are trained to minimise exposures.	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.	
Suitable mask with particle filter P3 (European Norm 143)	
Dermal - minimum efficiency of 98 %	
Inhalation - minimum efficiency of 98 %	
<b>Other conditions affecting workers exposure</b>	
Body parts exposed	: 960 cm <sup>2</sup>
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	
Process Temperature 123 °C	

### 8.2.5. Control of worker exposure: Treatment of articles by dipping and pouring (PROC13)

<b>Product (article) characteristics</b>	
Covers the percentage of the substance in the product up to 5%.	
Physical form of product	: Liquid mixture
<b>Amount used (or contained in articles), frequency and duration of use/exposure</b>	
Duration	: Exposure duration > 240 min
Use frequency	: Covers daily exposures up to 8 hours (unless stated differently).
<b>Technical and organisational conditions and measures</b>	
Ensure operatives are trained to minimise exposures.	
Use only in area provided with appropriate exhaust ventilation.	
Inhalation - minimum efficiency of 90 %	
<b>Conditions and measures related to personal protection, hygiene and health evaluation</b>	
Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.	
Suitable mask with particle filter P3 (European Norm 143)	
Dermal - minimum efficiency of 98 %	
Inhalation - minimum efficiency of 98 %	

**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

Other conditions affecting workers exposure	
Body parts exposed	: Palms of both hands (480 cm <sup>2</sup> )
Indoor or outdoor use	: Indoor
Assumes a good basic standard of occupational hygiene is implemented	
Process Temperature 123 °C	

**8.3. Exposure estimation and reference to its source**

**8.3.1. Environmental release and exposure: Industrial use of processing aids in processes and products, not becoming part of articles (ERC4)**

Protection Target	Exposure estimate	RCR
Fresh water	0.000007 mg/L (EUSES v2.1)	0.033
Marine water	0.0000007 mg/L (EUSES v2.1)	0.034
Fresh water sediment	0.000026 mg/kg dry weight (EUSES v2.1)	< 0.01
Marine sediment	0.0000027 mg/kg dry weight (EUSES v2.1)	< 0.01
Soil	0.0000003 mg/kg dry weight (EUSES v2.1)	< 0.001
Sewage treatment plant	< 0.0000001 mg/L (EUSES v2.1)	< 0.001

**8.3.2. Worker exposure: Use in closed process, no likelihood of exposure (PROC1)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.018 mg/m <sup>3</sup> (EASY TRA v4.1)	0.102
dermal	systemic	long-term	< 0.001 mg/kg bw/day (EASY TRA v4.1)	0.007

**8.3.3. Worker exposure: Use in closed, continuous process with occasional controlled exposure (PROC2)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.097 mg/m <sup>3</sup> (ECETOC TRA)	0.541



**ANDEROL 555**

Version 1.19      Revision Date: 05.10.2020      SDS Number: 000000007152      Date of last issue: 13.02.2020  
Date of first issue: 07.03.2014

dermal	systemic	long-term	0.003 mg/kg bw/day (ECETOC TRA)	0.069
--------	----------	-----------	---------------------------------------	-------

**8.3.4. Worker exposure: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities (PROC8b)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.110 mg/m <sup>3</sup> (ECETOC TRA)	0.609
dermal	systemic	long-term	0.008 mg/kg bw/day (ECETOC TRA)	0.165

**8.3.5. Worker exposure: Treatment of articles by dipping and pouring (PROC13)**

Exposure route	Health effect	Exposure indicator	Exposure estimate	RCR
inhalative	systemic	long-term	0.037 mg/m <sup>3</sup> (ECETOC TRA)	0.203
dermal	systemic	long-term	0.014 mg/kg bw/day (ECETOC TRA)	0.274

**8.4. Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

Fulfilling the above conditions the downstream user is deemed to work safely inside the boundaries set by this exposure scenario.

Other conditions should only be considered if the downstream user implements or recommends an exposure scenario which includes as a minimum the conditions described in this exposure scenario.